



Aluminium Communal Door Specification

Scope

- Single doorset
- · Inward or outward opening
- Pivot hinge
- RTS87 concealed top hung door closer
- 2no. stainless steel NSD5000 maglocks (1650lb holding force per magnet)
- 12mm ramped aluminium threshold
- 17 door configurations
- Glazed and solid top and side panels

Accreditation & Warranty

- Secured by Design approved
- Certified by the LPCB to LPS 2081 Security Rating B
- Supplied with a 10 year anti-rust warranty

Door Frame & Leaf

- Maximum door height 2200mm
- Maximum opening width 1200mm
- 3mm aluminium on external faces
- 450mm stainless steel door handle (straight or cranked)
- 500 x 67mm internal push plate
- 150mm high internal and external kick plates (width to suit door)

Seals

- Integrated glazing seal
- Integrated brush strips

Glazing / Infill Options

- 24mm thk sealed double glazed unit
- 6mm or 10mm thk polycarbonate
- 6mm or 10mm thk laminate
- Stainless steel solid infills

Side Panels

- Maximum height 1200mm
- Maximum width 2200mm
- Fully glazed panels (as per glazing options)
- Stainless steel solid panels

Top Panels

- Maximum height 1200mm
- Maximum width 2200mm
- Fully glazed panels (as per glazing options)
- Stainless steel solid panels






Manufacture & Installation

- Door leaf to be fully factory assembled
- Door frame to be fully factory assembled
- No specialist tools required for installation
- Nationwide delivery and installation service available

Configuration

Please note that these are shown with glazing panels, but any of these can be replaced with solid infill.



Finish

Newton communal doors are polyester powder coated in a choice of 9 colours with a textured finish, as standard. Other colours and finishes are available on request.

